


CBA4G-200D**0.8 GHz to 4.0 GHz 200 Watt P1dB Class A Solid State Amplifier****MAIN FEATURES**

- Class A Operation
- 100% Mismatch Tolerant with no Foldback
- Ethernet, USB, RS232 & GPIB Interface
- Built in Calibrated Directional Coupler
- 3 Year Warranty

Class A, high power density, design has allowed us to produce a 0.8 GHz to 4 GHz amplifier series with power levels from 30 to 800 watts P1dB. These amplifiers are ideal for RF immunity testing in a GTEM Cell or with a wide range of available horn antenna such as the Teseq BHA range or readily integrated with an NSG 6000 to form part of a broadband RF test system.

The touch screen colour display gives an immediate visual indication of forward and reverse power along with the current operating status of the amplifier and access to diagnostic information such as gate current and heatsink temperature.

Fan speed adjusts depending on the heatsink temperature thus ensuring the minimum audio noise level possible in the operating environment. The inbuilt calibrated forward power coupler provides a quick and easy way to monitor forward power with any power meter. Input overdrive protection prevents damage to the input devices due to accidental high input power. Multiple remote interfaces are available as standard including USB, GPIB, RS232, and Ethernet.



RF Specifications

Frequency (min.) GHz	0.8 GHz
Frequency (max.) GHz	4 GHz
Psat (min)	300 W
P1dB (min.)	200 W
Small Signal Gain	53 dB
Gain Variation (max) ±	+/- 3.0 dB
Harmonics @ P1dB (typ)	-20 dBc
Spurious (min.)	-70 dBc
3rd Order Intercept Point	10 dB > P1dB
RF Sample Port Coupling Factor (nom)	47 dB
Modulation Formats	AM, FM, PM, OFDM
Maximum Input Power (no damage)	10 dBm
Gain Control	0-30 dB in 255 Steps
Output VSWR Tolerance	Infinite any phase (no foldback)
Stability	Unconditional
Output Impedance	50 Ohm
Input VSWR	2:1 (max)
Output VSWR	2:1 (typical)

General Specifications

Safety Interlock	Via rear panel mounted BNC-female
Supply Voltage	180 to 264 VAC
Supply Frequency	47 to 63
Supply Power (typ.)	1.3 kVA
RF Input Connector	Type N female
RF Output Connector	Type N female
RF Sample Port Connectors	Type N female
Com. Interface	GPIB, RS232, Ethernet & USB
Weight kg	48 kg
Dimensions (WxHxD)	19 inch, 4U, 615mm
Cooling System	Air Cooled, Self-contained

Available Product Configurations

Product	Configuration	Item #
CBA4G-200D-001	Front Panel RF Connectors	3-342466
CBA4G-200D-002	Rear Panel RF Connectors	3-342467