



## MAIN FEATURES

- Coupling networks designed for IEC/EN 61000-4-6
- CDN M series for mains applications
- Models with frequency range 150 kHz to 80 MHz
- for 5 Lines application
- Models with terminal block
- with maximum current of 100 A

## CDN M5, 100 A from 150 kHz CDN IEC 61000-4-6

IEC/EN 61000-4-6 specifies the design and performance of a range of coupling / de-coupling networks (CDNs). Each CDN is specific to the type of cable and the intended signal carried on the cable. AMETEK CTS with its brand TESEQ offers an extensive range of CDNs which fully comply with the requirements of the standard and provide a simple and reliable method of injecting RF energy into the equipment under test (EUT). In this datasheet, CDN used with unscreened supply (mains) with five line applications with maximum of 100 A starting from 150 kHz as required by IEC/EN 61000-4-6 is presented.

The CDN M5 series is used to Inject common mode disturbance signal to supply lines for three line applications (with neutral and PE line) in the frequency range from 150 kHz to 80 MHz.

Verification results is supplied with each unit. Traceable and accredited calibration according to ISO17025 is available upon request. The CDN can be ordered alone or as a kit, which includes the necessary adapters for verification. please refer to the set order information for more details.



For safety, AMETEK provides a protective earth bolt attached to the bottom plate of all CDN series which can be used to connect it with ground.

Typical performance with limit lines for common mode impedance and voltage division factor can be found in this datasheet.

## Electrical Specifications

	CDN M5-100	CDN M5-100-750V
Frequency Range	150 kHz to 80 MHz	
Connector EUT Port	Terminal block	
Connector AE Port		
Line Parameters	5 power lines	
Application Configuration	(3L+N+PE)	
AC max. voltage (L-N) / (L-L)	300 V / 520 V	750 V / 750 V according EN 60998-1 and 600 V / 600 V according UL 1059
DC max. voltage (L-N) / (L-L)	400 V / 600 V	1000 V / 1000 V according EN 60998-1 and 850 V / 850 V according UL 1059
Current Max	100 A (max. 60 min)	100 A (max. 45 min)
Test Voltage, 2 sec.	3.1 kVDC	4.7 kVDC
Common Mode Impedance (EUT Port)	150 kHz to 24 MHz: 150 $\Omega$ $\pm$ 20 $\Omega$ 24 MHz to 80 MHz: 150 $\Omega$ +60 $\Omega$ / -45 $\Omega$	

### Typical Performance for Common Mode Impedance and Voltage Division Factor



### RF to EUT/AE Specifications

	CDN M5-100	CDN M5-100-750V
RF Port	BNC 50 Ω	
RF Voltage	< 30 V <sup>1</sup>	
Voltage division factor (RF input to EUT port)	150 kHz to 24 MHz: 10 dB ±1 dB 24 MHz to 80 MHz: 10 dB +2 / -1 dB	
Insertion loss (EUT / AE)	f < 400 Hz: <0.1 dB	
Decoupling of CM disturbance (RF port / AE) typ.	150 kHz: >20 dB 1.5 MHz: >50 dB 30 MHz: >40 dB 80 MHz: >20 dB	
Footnote	1. refers to 50 V test level in 300 Ω	

### General Specifications

	CDN M5-100	CDN M5-100-750V
Dimensions (WxHxD)	200 x 200 x 470 mm <sup>3</sup>	
Net Weight	approx. 12kg	approx. 12 kg
Operating Environment	Indoor use only	
Operating Temperature	+5°C to +40°C	
Humidity	up to 80%	

### Set Information

	CAL U100M 25713B	A50-N 257521	SAR M116 239915	SAR M500M 257146	SAR MA51M 257139
CDN M5-100S 257151	2	1	1	1	1
CDN M5-100-750VS 257163	2	1	1	1	1