

# NSG 438 FLAGSHIP ESD SIMULATOR OPTIMIZED FOR AUTOMOTIVE TESTING



- Air- and contact-discharge to 30 kV
- Battery tested to 30'000 discharges at 30 kV
- Color touch panel control
- Advanced voltage-hold feature
- Activity log
- Compliant with a huge range of OEM and international standards
- Built-in ISO self-calibration procedure
- Easily and quickly interchangeable discharge networks
- Selectable discharge detector

Ergonomic design and advanced functionality. The NSG 438 ESD simulator is designed to sit comfortably in the operator's hand, with operating conditions constantly displayed and accessible on a bright, clear color touch display.

NSG 438 comprehensively fulfills virtually all international standard requirements. Based on over 60 optional discharge networks, the NSG 438 can meet any of today's automotive manufacturers' standards.

The simulator is simple, convenient and safe to use. The whole range of parameter settings including polarity selection, freely adjustable pulse repetition, counter functions and discharge detection is available up to the maximum discharge voltage.

The color touch display and keypad for parameter input shows the precise functional and test data with user-selectable language for convenient and safe operation worldwide. The simulator contains variable threshold selection for accurate discharge detection. This detection feature can be switched off when testing EUT's with non-conductive surfaces, such as plastic housings. Pre-programmed settings for IEC 61000-4-2 and ISO 10605 ensure that the simulator is automatically set up correctly and the appropriate discharge network is installed. The actual RC value is displayed at all times. Molded HV discharge networks in solid cases eliminate ionization and leakage current effects. Precisely tuned combinations of RC components guarantee wave shape parameters to be within tolerances. A unique activity log is included so that the types and numbers of ESD simulations can be easily scrolled through to check what has been tested and in what timeframe.

The simulator is recalibrated and adjusted at every start, or with a simple tap of the screen. This built-in calibration and self-test feature, in conformance with the ISO standard can save considerable time.

For extra safety, an interlock and an emergency stop switch is built in. Additional features include freely adjustable pulse repetition rate, a special random generator function and an optional charge remover for discharging the EUT.

# NSG 438 FLAGSHIP ESD SIMULATOR

## OPTIMIZED FOR AUTOMOTIVE TESTING

### Technical specifications

Basic set:	Carrying case with: discharge pistol, cradle for discharge pistol, high voltage base unit with built-in battery pack, mains adapter and battery charging unit (100 to 250 VAC), discharge network 150 pF / 330 $\Omega$ , air- and contact-discharge tips, grounding cable, user manual, 25 mm discharge sphere
Pulse networks:	Network 150 pF / 330 $\Omega$ as per IEC/EN 61000-4-2 and ISO 10605 (included) Optional ISO 10605 networks 330 pF / 330 $\Omega$ , 150 pF / 2 k $\Omega$ and 330 pF / 2 k $\Omega$ Range of RC networks for other standards: R = 0 $\Omega$ to 20 k $\Omega$ ; C = 50 to 2000 pF
Discharge voltage:	Air-discharge: 200 V to 30 kV (in 100 V steps) Contact-discharge: 200 V to 30 kV (in 100 V steps)
Discharge tips:	Ball and point as per IEC and specials, exchangeable by threaded cap
Charging voltage measurement:	kV, accuracy better than $\pm 5\%$ (stabilized)
Discharge detection: (air-discharge only)	Indicated by the kV symbol being displayed in inverse also acoustically in the 'Single' operating mode. Adjustable threshold level.
Holding time:	> 5 s (charging voltage +5%)
Charge resistor:	50 M $\Omega$
Polarity:	Positive / negative / automatic change
Operating modes:	Single / repetitive / random (time / pulse) Pulse counter: 0 to 9999 Pre-select counter: 0 to 9999 Repetition: - 0.5 / 1 / 5 / 10 / 20, 25 Hz (air) - 0.5 / 1 / 5 / 10 H or 20 Hz (contact) - freely selectable from 0.04 to 300 s - continuous operation
Display:	LCD panel showing: charging voltage, breakdown event, polarity air- / contact-discharge, counter / preselect counter content, network parameters, battery monitor
Weight:	Discharge pistol (w/o cable): 1.2 kg (2.6 lbs) approx. Base unit: 6.5 kg (14.3 lbs) approx.
Ambient conditions:	Operation: +5 to +40°C, 20 to 80% r.h. (non-condensing), 68 to 106 kPa
Accessories:	The full accessory range such as discharge network special tip E- and H-field adapter and ESD measurement target can be found in the brochure.

**AMETEK CTS GmbH**  
Sternenhofstrasse 15  
4153 Reinach  
Schweiz  
sales.cts.eu@ametek.com

© March 2021  
Specifications subject to change without notice. AMETEK CTS® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, AMETEK CTS does not assume any liability for errors or inaccuracies.